



## NEW PRODUCT SUPPLEMENT

ELECTRIC HEATING PRODUCTS • HEATING • SHOWERS • WATER HEATING

2019

## 2 TORNADO DUO



### FEATURES

- Adjustable settings for increased energy efficiency
- Low noise levels in operation
- 10 second drying time
- Dual sensor activation for instant start
- Fitted HEPA filter
- 600W low energy motor
- Selectable 1400W heating element (2000W)
- Selectable air flow setting
- Fully automatic operation
- Tamper proof controls
- Brushed Stainless Steel and White Finish



See our full range of Hand Dryers on pages 48 - 51 of the Heatstore 2018/2019 catalogue

| PRODUCT | RATING       |            | WEIGHT | DIMENSIONS  |            |            | AIR SPEED | NOISE | COLOUR          | IP RATING |
|---------|--------------|------------|--------|-------------|------------|------------|-----------|-------|-----------------|-----------|
|         | Unheated (W) | Heated (W) |        | Height (mm) | Width (mm) | Depth (mm) |           |       |                 |           |
| HS5750  | 600          | 2000       | 5.9    | 325         | 310        | 188        | 90        | 75    | Stainless Steel | IPX1      |
| HS5750V | 600          | 2000       | 5.9    | 325         | 310        | 188        | 90        | 75    | White           | IPX1      |

# BOILING & AMBIENT FILTERED WATER TAP 3

The new Heatstore Boiling Water Tap is the ideal solution for a commercial or domestic property where the customer is looking to reduce energy. The tap provides instant boiling water for hot drinks but also ambient filtered water for a purer drinking water supply.



## FEATURES

- Filtered boiling water
- Filtered ambient water
- Touch sensitive start/stop
- Visual indication for boiling water
- Supplied with universal 3M filter
- Easy to fit and install
- Digital filter life time display
- 105 cups per hour
- Tank capacity: 2.5 Litres
- Power: 1.5kW @ 230V
- Time to heat up from cold: - 10 Minutes
- Stainless steel tank
- Anti scale design
- Adjustable temperature thermostat



EXCHANGE  
WARRANTY



IPX4



DOUBLE  
INSULATED



|      | DIMENSIONS (TAP) |            |            |
|------|------------------|------------|------------|
|      | Height (mm)      | Width (mm) | Depth (mm) |
| TAP  | 352              | 42         | 128        |
| TANK | 348              | 210        | 295        |

| PRODUCT  | RATING | CAPACITY | HEAT UP TIME | DRAW OFF  | WEIGHT | IP RATING | MAXIMUM INLET WATER PRESSURE | MAXIMUM WATER TEMPERATURE |
|----------|--------|----------|--------------|-----------|--------|-----------|------------------------------|---------------------------|
|          | (W)    | (L)      | (mins)       | (cups/hr) | (Kg)   |           | (bar)                        | (°C)                      |
| HSBWT025 | 1500   | 2.5      | 10           | 105       | 6      | IPX4      | 5                            | 98                        |

# 4 TOTAL CONTROL “LIVE” CONTROLLERS



HSMLCRF MASTER LANDLORD CONTROL

## FEATURES

- Wirelessly controlled
- Can control an unlimited number of HSSLCRF (depending on the building construction)
- Option to limit min/max temperature
- Limit user override time
- 7-day programme timer
- 6 time settings per day
- Simple to set up and easy to programme
- Large backlit LCD display for easy reading
- Stylish and sleek modern design
- Temperature display of either °C or °F
- 2 operating modes

## FUNCTIONS

Room occupants can temporarily adjust the room temperature using the HSSLCRF for a predetermined length of time reverting back to the programmed temperature set by the HSMLCRF.



HSSLCRF SECONDARY LOCAL CONTROL

## FEATURES

- Wirelessly controlled
- Mains or battery powered
- Open window detection
- Allows user to temporarily increase or decrease the room temperature
- Can control multiple heaters in a room
- Large backlit LCD display for easy reading
- Stylish and sleek modern design

## FUNCTIONS

Room occupants can temporarily adjust the room temperature for a predetermined length of time up to 4 hours.

The controller will then revert to the fixed temperature set by the HSMLCRF.



See our Total Control Brochure for our full range of RF products

| PRODUCT | DIMENSIONS  |            |            |
|---------|-------------|------------|------------|
|         | Height (mm) | Width (mm) | Depth (mm) |
| HSMLCRF | 99          | 136        | 23         |
| HSSLCRF | 99          | 136        | 23         |



# TOTAL CONTROL “MANUAL” CONTROLLERS 5



HSVTBRF

## FEATURES

- Wirelessly controlled
- Battery Powered (2 x AAA batteries supplied)
- 3 operating modes: Manual, Timer and Temperature Control
- 4-stage run back timer with choice of 3 time periods: 5, 15 or 30 minutes
- Comfort setting to maintain temperature
- Variable thermostat temperature control
- Easy-to-read digital display
- One controller can control many heaters



HSBRRF BOOSTER / RECEIVER UNIT

## FEATURES

- Wireless control conversion of most electric heaters
- System range booster
- Can control up to a 3kW load
- Maximum switching current 13A/250V
- Can be retrofitted to existing compatible heaters



HSTIRFN

## FEATURES

- Wirelessly controlled
- 7 day timer
- Mains or battery powered
- Option to limit min/max temperature
- Open window detection
- Allows user to temporarily increase or decrease the room temperature to pre set limits
- Can control multiple heaters in a room
- Large backlit LCD display for easy reading
- Stylish and sleek modern design
- Simple to set up and easy to programme
- Temperature display of either °C or °F

See our Total Control Brochure  
for our full range of RF products



EXCHANGE  
WARRANTY



RF WIRELESS



ZONE U

| PRODUCT | DIMENSIONS  |            |            |
|---------|-------------|------------|------------|
|         | Height (mm) | Width (mm) | Depth (mm) |
| HSTIRFN | 89          | 136        | 23         |
| HSVTBRF | 88          | 85         | 26         |
| HSBRRF  | 87          | 80         | 57         |



# 6 TOTAL CONTROL CONVECTOR HEATERS



**HSCVDRF CONVECTOR  
HEATER WITH BUILT IN DEFLECTOR**

## FEATURES

- Wirelessly controlled
- Wall mounted
- Built in heat deflector
- 2kW rating
- Virtually noiseless operation
- Automatic safety cut-out
- LED indicator light
- Finished in white
- Fitted with 1.8m of supply cable



**HSCVDURF CONVECTOR  
HEATER UNDER TRUNKING**

## FEATURES

- Wirelessly controlled
- Wall mounted
- Built in heat deflector
- Designed to be installed under trunking
- 2kW rating
- Virtually noiseless operation
- Reduced risk of wall staining and delamination
- Full length wall bracket for ease of installation
- Automatic safety cut out
- LED indicator light
- Finished in white
- Fitted with 1.8m of supply cable



**HSCVFRF CONVECTOR  
HEATER WITH FAN**

## FEATURES

- Wirelessly controlled
- Wall mounted
- Circulates the warm air quicker
- Built in low noise fan
- 2kW rating
- Quiet operation
- Reduced risk of wall staining and delamination
- Full length wall bracket for ease of installation
- Automatic safety cut out
- LED indicator light
- Finished in white
- Fitted with 1.8m of supply cable



EXCHANGE  
WARRANTY



2000W



RF WIRELESS



ZONE U


See our Total Control Brochure  
for our full range of RF products

| PRODUCT  | RATING | WEIGHT | DIMENSIONS  |            |            | SOUND LEVEL |
|----------|--------|--------|-------------|------------|------------|-------------|
|          | (W)    | (Kg)   | Height (mm) | Width (mm) | Depth (mm) | dB(A)       |
| HSCVDRF  | 2000   | 3.9    | 360         | 590        | 130        | -           |
| HSCVDURF | 2000   | 3.9    | 360         | 590        | 130        | -           |
| HSCVFRF  | 2000   | 5.2    | 360         | 590        | 130        | 40          |

# DOWNFLOW HEATERS 7



**HSBH2RF BATHROOM  
DOWNFLOW FAN HEATER**



| PRODUCT | RATING | WEIGHT | DIMENSIONS  |            |            |
|---------|--------|--------|-------------|------------|------------|
|         | (W)    | (Kg)   | Height (mm) | Width (mm) | Depth (mm) |
| HSBH2RF | 2000   | 3.9    | 360         | 590        | 130        |

## FEATURES

- Wirelessly controlled
- 2kW rating
- Automatic safety cut out
- LED indicator light
- Fitted with 0.9m of supply cable
- Fixing/Securing bracket
- Wireless controlled by separately purchased RF or CRF controller
- One RF or CRF controller can operate multiple RF heaters
- Choice of controllers:  
HSPBRF: Run-back timer and thermostat  
HSVTRF: Run-back timer and adjustable thermostat  
HSTVTRF: Battery-powered run-back timer and adjustable thermostat  
HSTIRFN: Programmable 7-day timer and thermostat
- 2 automatic safety cut-outs for additional safety
- Fitted power supply cable
- LED indicator light
- Secure wall fixing
- Finished in white



**HS2000T 2KW DOWN FLOW  
HEATER WITH RUN BACK TIMER**



## FEATURES

- Suitable for use in bathrooms and en suites
- Energy saving 30 minute run back timer
- 1kW or 2kW option (set on installation)
- Pull cord operation
- Neon indicator
- Pre-set thermostat
- Double insulated construction

| PRODUCT | RATING | WEIGHT | DIMENSIONS  |            |            | CONTROL | CUT OUT | THERMOSTAT RANGE | IP RATING | STAND BY MODE |
|---------|--------|--------|-------------|------------|------------|---------|---------|------------------|-----------|---------------|
|         | (W)    | Kg     | Height (mm) | Width (mm) | Depth (mm) |         |         | °C               |           | kW            |
| HS2000T | 2000   | 1.1    | 242         | 229        | 109        | Manual  | Manual  | 5 - 35           | IP22      | 0.002         |

[www.heatstore.co.uk](http://www.heatstore.co.uk) for all product information

tel 0117 923 5375 fax 0117 923 5374 Unit 12, Access 18, Bristol BS11 8HT

The logo for Heatstore, featuring a red square icon with horizontal lines to the left of the word "HEATSTORE" in a bold, sans-serif font. The word "HEAT" is red and "STORE" is grey. The entire logo is enclosed in a red rounded rectangle.

**HEATSTORE**